

## TECHNICAL INFORMATION

Edinburgh Corn Exchange

### Parking

Adequate secure parking within compound available for equipment, artists and crew.  
There are no restrictions on parking on any adjacent roads.

Parking capacity within compound: 370 spaces

### Loading

Access from New Mart Road. Rear double doors directly behind the stage.

Loading Bay and ramp straight into main hall, accessed by electrically operated roller doors

clear height 2.4 m

clear width 2.7m

### Sound Levels

The building is designed to contain a noise level of:

octave band spl	limit
63	94
125	98
250	101
500	107
1k	106
2k	102
4k	92
8k	89

### Power

Stage 1 supply (lighting) 125 amp 3 phase

Stage 2 supply (sound) 63 amp 3 phase

## **Dressing Rooms**

There are four dressing rooms with showers, typical usage:

star 1 - band

star 2 - support

star 3 - support

star 4 – production

Artist lounge also available plus kitchen.

After show Bar/ Function suite available on request

## **Staging**

Stage provided by venue is 40ft x 20ft, with a height of 4ft. It is positioned 2.5m from the back wall, a limited number of risers are available for stage left and right.

Barrier provided by the venue and is positioned 1.5m from front of stage. The aforementioned layout is agreed by public safety and will not be altered or obstructed by position of speakers or other 'band' material ( band material can also mean any equipment provided for exhibition or conference to guarantee maximum occupancy. This is a material part of contract to occupy.

Curtains for stage areas are not provided by venue (can be provided at an extra cost) and promoter must provide current certification of all drapes to be used no later than 24 hours before start of concert. The venue will take into consideration the request of the artist and prepare the positions asked for in respect to mixer and spot positions.

A gallery area is also available

## **Hanging Points**

Above and front of stage, 4 beams plus 4 x 2 tonne girder clamps in position for main support - each beam has 3 further flying hooks spaced 2m, 3.6m, 3.6m, 2m each capable on 1 tonne loading.

Safe working load of each beam is 3 tonnes. Additional girder clamps can be positioned throughout hall at beam positions.

## **EXHCHANGE DIMENSIONS**

1372 square metres

49m x 28m

Ceiling height: 6.6m in centre, 3.3m at sides of room

Maximum capacity: 2800 standing, 1300 seated

The hall can be draped to accommodate smaller events.